

MAXIMUM

MAX

CONTROLS



MAX PHANTOM F6
HIGH TRAFFIC COMMERCIAL
BRUSHLESS DC SWING GATE OPERATOR
CONTROLLING GATES TO THE MAXIMUM LEVEL

Low profile ... Super Fast ... High Performance



325/991 Compliant



MAX PHANTOM F6

FEATURE LIST:

Mechanical Specifications

- ✓ Lowest profile design in the industry, ONLY 15½" tall
- ✓ Max Phantom F6 dimensions (22" W x 18 ¾" D x 15½" H)
- ✓ Heavy duty gear box 500:1 Size 80 constant lubrication using special gear oil
- ✓ Opens gates up to 1000lb/15ft (sold as dual only)
- ✓ Large output shaft 3¼" solid steel with cast iron clamping system
- ✓ Fast speed direct drive (no chains, belts, or pulleys) opens gate 90 degrees from 6 to 10 seconds based on weight of the gate and selectable speed control
- ✓ Mechanical and electrical manual gate release functions
 - Dual layer corrosion protection gold zinc and powder coating
 - Built-in loop rack
 - Gate operator shipping weight 216½ lbs including operator, 1 control box, and 1 swing arm and battery module
- ✓ Continuous cycle at extreme temperature range. No overheating possibility
- ✓ Intelligent ramp-up and ramp-down gate speed control for smooth operation

Electrical Specifications

- ✓ Brushless DC motor equivalent to 1 HP AC motor
- ✓ Programmable gate speed controls, 16 selectable speeds
 - Automatic gate position reset system
- ✓ Auto gate sync feature provides synchronous opening and closing between two gates
- ✓ Modular system design for ease of service
- ✓ Switchable 115/230 voltage selection
- ✓ Adaptive DSP control for advanced brushless DC motion control
- ✓ Real time performance analyzer and event log (OBD PORT and Black Box)
- ✓ Low voltage wiring capabilities for remote power up 1000 feet (no battery needed)
- ✓ Solar ready battery module with built-in advanced solar regulator
- ✓ Intelligent power management system with energy saver mode
 - Built-in current limited 12vdc and 24vdc outputs
- ✓ Gold contact input connections and automobile grade connectors
 - Selectable open timer 0 to 60 seconds with timer off option
 - -4F to 165F (-20C to +74C) operational temperature range including battery performance without needing a heater
- ✓ Robust lightning protection up to 20KVolts and 10KAmps on all inputs and outputs
 - (44 Channels) including loop detector input connections
- ✓ Tunable 16 position safety obstruction sensor, adaptable to gate weight and size
- ✓ Dual motor overcurrent safety shut off for additional protection
- ✓ = Unique to Max Phantom F6

- Every operator includes a Max BC-7 battery module with over 400 cycles in case of power failure
- ✓ Three modes of selectable battery backup functions
- ✓ State-machine design electronics with ultra-fast microprocessor
- On board three button station

Security Specifications

- ✓ High traffic intuitive loop management system for better security
- ✓ Advanced security features with built-in audible and remote alarms
 - Magnetic lock control relay outputs with selectable delay times
- ✓ Tamper alert relay outputs triggered “on” if gate is forced open
- ✓ Audible alarm if gate is tampered with or ERD is triggered for higher security
- ✓ Gate partial open recorder
- ✓ Lockable cover with key lock release to prevent intruders and vandals
- ✓ Gate disable feature, disables all inputs with exception of the fire department input for high security
- ✓ Built-in transaction buffer for high security
- ✓ Gate status outputs for gate monitoring
- ✓ Direct motor control of jog OPEN/CLOSE for manually moving a gate in case of emergency
- ✓ Advanced anti-tailgate features to provide higher security
 - No need for magnetic lock with the robust output shaft and clamp design of the Max Phantom F6

Safety Specifications

- Adaptive obstruction sensor for much better gate safety system. 16 selectable sensitivity settings
- Built-in UL buzzer reset
- UL 325 Class of operation I, II, III, and IV. CSA approved
- Pinch arm protection design
- ✓ Magnetic dynamic brake system stops the gate immediately to prevent damage to obstructions
- ✓ Vehicle hit protection technology protects the gate operator from collision damage caused by automobile impact
- ✓ Built-in advanced entrapment protection and alarm output
 - Built-in gate in motion alarm for industrial applications

- ✓ = Unique to Max Phantom F6

THE MAX PHANTOM F6

Low profile gate operator measures an astonishing 15.5 inches to the top of the swing arm cap, making it the lowest profile gate operator on the market.



The Phantom can be hidden behind shrubs or landscaping to help architects keep the focus off the operators and on the gates. The Max Phantom F6 operator is also compatible with existing installations and in most cases can be directly bolted onto concrete pads used by the most popular gate operators in the industry.



CHASSIS

Corrosion control is not the most exciting topic, but can make all the difference when manufacturing an outdoor product. All gate operators are exposed to harsh climates. Temperature, moisture, and proximity to salt water will speed the rate of corrosion and compromise the structure. To guard against this corrosion, the Phantom F6's chassis is treated with two layers of protection.

First the steel is coated with gold zinc, then, an electrostatic powder coating is applied. The cold rolled steel frame, which will not fracture under stress, is designed to withstand tremendous amounts of torque.



GEARBOX


The Max Phantom F6 implements a size 80, 500:1 high efficiency gearbox. This 500:1 ratio produces maximum torque, utilizes low amperage, and provides super silent operation. The rugged cast iron housing, bronze gears, and double sealed heat treated solid shafts have been designed by a team with over 40 years of experience in the gearbox industry.

High speed ball bearings and a synthetic oil bath keep the dual gear reduction operating flawlessly through extreme temperature ranges. We invite you to compare our Maximum Controls gearboxes to any of those used by other manufacturers in the industry.

MODULES

The Max Phantom F6 uses interchangeable modules that are functional in any Maximum Controls gate operator. Modules such as motor controllers, logic boards, limit boxes, and even battery boxes can be swapped from one operator to another regardless of the gate operator model number.

This standardization of modules and interchangeability, coupled with the intelligence of our operating system offers a benchmark to which future gate operators will strive to achieve.



MOTOR CONTROLLER


Each Max Phantom F6 operator has a motor controller. Maximum Controls proprietary motor control technology learns the physical characteristics of a gate in order to control motion with maximum efficiency and speed. The adaptive motor control of the Phantom also facilitates precision synchronization of two gates that might not be of equal weight or length. In addition to communicating with two motor controllers, a single Matrix 1 logic board allows for variable speed control within learned speed parameters.

The motor controller, using DSP technology, monitors all currents and voltages enabling 16 programmable levels of electronic obstruction sensing.



BRUSHLESS DC MOTOR

The brushless DC motor in the Max Phantom F6 uses “Hall Effect” magnetic sensing to identify over five thousand precise rotational positions during 90 degrees of gate movement. That’s over 50 samples per degree of gate travel. Using this positional feedback, intelligent ramp-up and ramp-down of the gate speed is employed to minimize undue stress on all mechanical components.



Utilizing the monitoring and updating of positional data, a solid sync of two gates can be realized. This constant updating is also used to detect any unauthorized movement.

The 24VDC operating voltage of the brushless DC motor permits operation via a remote power supply. In this “low voltage mode,” the Max PS-24 power supply can be located up to 1000 feet away making installation far less costly and easier than traditional 120VAC trenching.

ADVANTAGES OF BRUSHLESS DC MOTOR

FEATURE	BRUSHED DC MOTORS	BRUSHLESS DC MOTOR MAX
Commutation	Mechanical	Electrical
Maintenance	High	Very Low
Electronic Noise EMI	High	Super Low
Life	Short	Much Longer 6,000,000 Cycles
Speed/Torque Characteristics	Moderately Flat	Flat (Enables Operation at All Speeds)
Efficiency	Medium	High
Motor Speed	Limited Speed Control	Variable Speed Control
Audible Noise	High at High Speeds Because of Brushes	Super Quiet
Drive Complexity	Inexpensive	Advanced DSP Control
Loss of Torque Due to Aging	Yes	No
Energy Consumption	Higher	Lower
Magnetic Hall Sensors	No	Yes (5000 Samples Per 90 Degrees)

DIRECT DRIVE

Direct gear drive means there are no pulleys, belts, or chains required. Pulleys, belts, and chains are historic weak points of gate operators and require frequent service and maintenance calls.



OUTPUT SHAFT

The Max Phantom F6 has a 3.25 inch solid steel output shaft. This shaft along with heavy duty cast iron clamps provide the necessary clamping force to move the heaviest gates while providing a braking mechanism if the gate is struck by a vehicle. The massive shaft clamp assembly requires no shear pins or plates that are damaged by unintentional impact. If a gate controlled by the Phantom is struck, an intelligent reset system automatically recovers gate and limit positions. This means no costly maintenance or service fees. This serious clamp and output shaft design also makes the use of magnetic locks unnecessary.



CONTROL BOX

If any access is denied because of a system failure (remote control, keypad, or logic board/Matrix 1 malfunction) a manual system override is available in the form of a jog open/close switch. This jog switch, along with UL reset button, is located on the external control cover and an additional switch added near the entry keypad will ensure you are never locked out due to system failure.



MECHANICAL RELEASE

The Max Phantom F6 provides a quick and easy means to release any gate without compromising security. The lockable swing arm cap protects from unauthorized release of the gate arm. Once the cap is removed, the arm is easily released by pulling up the quick release handle.



POWER SUPPLY

A key benefit of the Max Phantom F6 modular design is the ability to separate modules. The power supply module, for example, can be removed from the main chassis and installed up to 1000 feet away from the operator. Regardless of whether the battery is installed or the Max PS-24 is remote, the gate remains fully operational (the battery module is used only for backup operation). This feature can save thousands of dollars in trenching and costly permit fees. Unforeseen complications like rock formations or utility lines that have to be trenched around can be avoided by using a power management system that does not rely on battery power. As a result, the battery life is not compromised. The Max PS-24 is designed for extended life in extreme temperatures. These technologies are unique to only Maximum Controls products.

In addition, operation of the Max Phantom F6 can save on energy costs. The average AC operator in a high traffic environment can cost as much as \$700 a year. A similar facility using the Phantom can save as much as 85% on the gate energy cost.



UPS BATTERY BACKUP

The Max Phantom F6 battery module, the Max BC-7, contains many features necessary for gate operation during power outages and provides safe, smart trickle charging to keep the batteries ready for emergencies or overnight in off grid use. In addition to serving as backup power during emergencies, the BC-7 contains the electronics to properly integrate a solar panel into an off grid configuration. Yes, the BC-7 supplies an on-board solar regulator as standard equipment.


Starting with the Max BC-7 front plate, a three LED gas gauge showing the current battery status—full, half, or empty is provided. This gauge also moves sequentially to indicate that the batteries are currently charging. A battery test status button, when pressed, gives you the actual condition of the batteries. Are the batteries a go or no go? No guess work here. You will know when the batteries must be replaced. When an outage does occur, an audible beep can be switched on to indicate battery backup in use.

On the Matrix 1 board there are three modes of battery backup functionality. “Leave gate open” will continue to open and close the gate until the battery is near empty and leave the gate in the open position. “Leave gate closed” will continue to open and close the gate until the battery is near empty, then leave the gate closed. “Open one time” will leave a gate in the open position immediately if an outage occurs. Regardless of the battery backup mode, enough energy is left in the batteries to open the gate for an emergency vehicle.

SOLAR READY POWER

In an off grid configuration, in addition to the solar regulator, the Max BC-7's solar processing circuitry provides a power boost, maximizes energy harvest, and keeps a tight grip on the load control ensuring the up to 200 watt solar panel is manipulated to its potential. Maximum Controls operators work with 80 watt panels or greater depending on the specific application. Standard 200 watt panels are supported and recommended. The solar in on the BC-7 requires 24 to 35VDC.

Each Max BC-7 battery module is fitted with Yuasa batteries with an operational temperature range of -4 to 165F. These batteries offer high-energy density, sealed leak proof construction, excellent performance in float of cyclic applications, maintenance free, rechargeable, and long service life. When used with the Max Phantom F6 they offer 400 cycles of duty before discharge.



BLACK BOX, LOOP MANAGEMENT, AND SECURITY

One of the primary goals of the Max Phantom F6 is to provide a secure easily maintained gate operator with higher gate speed motion and advanced loop management.

The Phantom uses non-volatile memory to continuously log performance characteristics and input/output events. A service technician can access this data via USB port to download the event history, quickly diagnosing complex or intermittent problems that have been very difficult to isolate and repair in the past. A thumb drive plugged into the USB, with all history downloaded, acts as a "Black Box" to find out what happened. The Phantom's event history is stored as a .TXT document which can be emailed to the factory for, if necessary, on site diagnosis. The .TXT file is a log of the most recent 1000 events reported by each module to the central logger.

The Phantom F6's standard intuitive loop management system, when enabled, will discourage tailgating and increase security for residential and high traffic installations. When the Anti-Tailgate switch is activated, any car tailgating a legitimate access will be forced to stop by a rapidly closing gate, forcing the tailgater to back up and thereby triggering the gate to close and deny unauthorized access.


When disabled, loop management will allow multi access, with the gate opening on each successive trigger in the traditional loop management manner.



ADVANCED SECURITY FEATURES:

Anti-Vandalism/ Burglar Alarm

As a security device, the Max Phantom F6 supplies a gate tamper relay output that triggers whenever a gate has encountered an unauthorized movement. This can be configured to activate an alarm system or camera. The Phantom F6 also has a gate disable feature which can disable operator function during a vacation or overnight for commercial applications.



- Battery Backup Mode Switch Selection
- Primary and Secondary Gate Designation
- Magnetic Lock Delay Selectable Switch with Relay Outputs
- Loop Inputs with LED Indicators
- Anti-Tailgate Selector Switch
- On Board Three Button Station
- Motor Speed Control
- Motor Error Indicators
- UL Alarm Output and Reset
- Gate Status Outputs and Indicators
- 12vdc and 24vdc Limited DC Power Output
- OBD / Black Box USB Port



- Motor Overload Indicator
- Obstruction Electronic Reversing Detection (ERD) Indicator
- ERD Sensitivity Adjustment
- Jog Open/Close switches
- Safety and External Jog Switch Inputs
- Communication Indicators
- Safety Indicators
- Power Indicator

LIGHTNING PROTECTION



The Max Phantom F6 offers the most robust lightning protection available in the industry. The Phantom F6 protects all peripheral inputs, loop inputs, power inputs, relay outputs, and all communication lines (over 44 channels of protection) in $1/1,000,000,000$ of a second. With special emphasis on power supply protection, the Phantom F6 is guaranteed to withstand any lightning hit more than 50 feet away. Truly protected like no other operator in the world.

Maximum Controls LLC Warranty and Return Policy Max Phantom F6

Section I Coverage

- a. 5 years on all components
- b. 1 year on batteries

Section II Not Covered

- a. Damages due to flooding
- b. Damages due to fire
- c. Damages due to negligence i.e. leaving the cover off in the rain, improper wiring of AC or peripheral systems
- d. Damages due to product misuse i.e. gate and operator combination mismatch
- e. Damages due to vandalism

Section III RMA Shipping Policy

- a. Maximum Controls LLC will pay for return shipping via standard ground UPS or USPS FOB CA on all RMA's within one year of Distributor's purchase
- b. Any form of "Expedited Shipping" on any RMA will be paid by Distributor

Section IV Product Returns

- a. Products must be in original, resalable condition with all warranty information, manuals, and original packaging.
- b. A re-stock fee of 10% will be charged on all returned products.
- c. All returned products must reference a Maximum Controls RMA number or it will be refused.
- d. Maximum Controls is not responsible for freight charges associated with returned merchandise.



www.Max.US.com

Maximum Controls, headquartered in Southern California, has over thirty-three years of experience in the design and manufacturing of gate operators, telephone entry systems, and other perimeter security products for the access control industry. The team of professionals at Maximum Controls has a long and successful history as sales leaders and industry innovators. For the past four years it has been the sole focus of Maximum Controls to design the fastest, most secure, most reliable, and safest gate operators in the world. "I will not compromise quality," I overheard Alex Parsadayan CEO of Maximum Controls saying to a customer. This philosophy has produced machines capable of great things. Gold plated inputs and outputs, automobile grade electronics throughout, cold rolled steel frames, massive cast iron gearboxes, output shafts and mechanical release assemblies so solid and heavy they're sure to last for years. Longevity at a competitive price—that's the key. Please compare Maximum Controls' features, warranty, and innovations when shopping for a product. Conceived as the next generation in Access Control technology, Maximum Controls has designed the most advanced gate operators ever built.



Maximum Controls LLC
949.699.0220
10530 Lawson River Ave.,
Fountain Valley, CA 92708 USA

Independent Dealer or Distributor